

TRANSPORTATION 611HT



Markets



611HT

Transportation

SAE J517 / 100R6 EN 854 TYPE R6

Performance



| # Part Number | Hose I.D. | | Hose O.D. | | Working Pressure | | Minimum Bend Radius | | Weight | | Vacuum Rating | | Parkrimp HY Series |
|------------------|-----------|------|-----------|------|------------------|-----|---------------------|-----|--------|------|-----------------|-----|-----------------------|
| | inch | mm | inch | mm | psi | MPa | inch | mm | lbs/ft | kg/m | inches of Hg | kPa | |
| 611HT-4 | 1/4 | 6,2 | 0.47 | 11,9 | 400 | 2,8 | 2 1/2 | 65 | 0.09 | 0,13 | 28 | 95 | ● |
| 611HT-6 | 3/8 | 9,3 | 0.59 | 15,1 | 400 | 2,8 | 3 | 75 | 0.11 | 0,16 | 28 | 95 | ● |
| 611HT-8 | 1/2 | 12,5 | 0.75 | 19,0 | 400 | 2,8 | 4 | 100 | 0.18 | 0,27 | 28 | 95 | ● |
| 611HT-10 | 5/8 | 15,7 | 0.88 | 22,2 | 350 | 2,4 | 5 | 125 | 0.19 | 0,28 | 18 | 61 | ● |
| 611HT-12 | 3/4 | 18,8 | 1.00 | 25,4 | 300 | 2,1 | 6 | 150 | 0.254 | 0,36 | 18 | 61 | ● |

Application: Petroleum base hydraulic fluids and lubricating oils, diesel fuels and antifreeze solutions.

Inner Tube: PKR®.

Reinforcement: One fiber braid.

Cover: Synthetic rubber abrasion resistant, MSHA accepted.

Temperature Range: -55°F to +302°F (-48°C to +150°C).

Fittings: HY Series - pg. B-132.

- See Section B for Field Attachable Assembly Instructions.
- See Section C for Parkrimp Assembly Instructions.
- Temperature Range of other media listed in Section E.