


# HYDRAULIC

# 722

## Markets



Parker's GlobalCore 722 spiral hose provides 4,000 psi (28 MPa) constant working pressure in sizes -6 through -16. Designed for high-pressure, high-impulse applications, 722 hose is offered in Standard, Tough Cover and Super Tough cover options. It is one-half the bend radius of 100R12 hose, making it easy to install and reducing the amount of hose needed. Meeting the ISO 18752 performance specification, Parker's 722 hose excels in multiple applications around the world.

- ½ ISO 18752 minimum bend radius
- 4,000 psi constant working pressure
- Exceeds ISO 18752 performance specification (BC and CC)
- 4-spiral construction for longer life in high-impulse, heavy-duty cycle applications
- TC cover provides 80 times the abrasion resistance compared to Standard rubber cover hoses
- ST cover provides 450 times the abrasion resistance compared to Standard rubber cover hoses

## Performance



## 722 Hydraulic – Constant Working Pressure ISO 18752 - BC/CC



# Part Number	ISO 18752 Performance			Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp 43 Series
	Standard Cover	Tough Cover	Super Tough	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	
	722	722TC	722ST											
722-6	BC	CC	CC	3/8	10	0.78	19,9	4000	28,0	2-1/2	65	0.40	0,60	●
722-8	BC	CC	CC	1/2	12,5	0.89	22,7	4000	28,0	3-1/2	90	0.54	0,80	●
722-10	BC	CC	CC	5/8	16	1.04	26,4	4000	28,0	4	100	0.74	1,10	●
722-12	BC	CC	CC	3/4	19	1.21	30,7	4000	28,0	4-3/4	120	0.94	1,40	●
722-16	BC	CC	CC	1	25	1.50	37,8	4000	28,0	6	150	1.34	1,99	●

**Application:** Petroleum base hydraulic fluids and lubricating oils

**Inner Tube:** Synthetic rubber

**Reinforcement:** Four-spiral steel wire

**Cover:** Standard Cover: Synthetic rubber

ToughCover: Synthetic rubber abrasion resistant

SuperTough: Synthetic rubber super abrasion resistant

**Fittings:** 43 Series - pg. B-25.

**Temperature Range:** Standard Cover: -40°F to +212°F (-40°C to +100°C) - BC  
ToughCover & SuperTough: -40°F to +257°F (-40°C to +125°C)

A

B

C

D

E