




Performance



722LT

Low-Temperature Spiral

SAE 100R12 / ISO 3862-1 Type R12 / EN 856 Type R12

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp	Parkrimp
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	43 Series	71 Series
722LT-6	3/8	10	0.78	19,8	4000	28,0	2-1/2	65	0.40	0,60	•	
722LT-8	1/2	12,5	0.89	22,6	4000	28,0	3-1/2	90	0.54	0,80	•	
722LT-10	5/8	16	1.04	26,4	4000	28,0	4	100	0.74	1,10	•	
722LT-12	3/4	19	1.21	30,6	4000	28,0	4-3/4	120	0.94	1,40	•	
722LT-16	1	25	1.49	37,7	4000	28,0	6	150	1.34	1,99	•	
722LT-20	1-1/4	31,4	1.82	46,2	3000	21,0	8-1/4	210	1.74	2,59	•	
722LT-24	1-1/2	38	2.06	52,5	2500	17,5	10	250	2.01	2,99		•

Application: Snow grooming equipment; heavy construction equipment; sidebooms.

Inner Tube: Nitrile synthetic rubber.

Reinforcement: Four spiral steel wire.

Cover: Synthetic Rubber.

Temperature Range: -70°F to +212°F (-57°C to +100°C).

Fittings: 43 Series, sizes -6 to -20 - pg. B-25.
71 Series, size -24 - pg. B-69.



Performance



792LT

Low-Temperature NO-SKIVE

SAE / ISO – Exceeds SAE 100R15 / ISO 3862-1 Type R12 / EN

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	79 Series
792LT-16	1	25	1.52	38,7	6000	42,0	13	300	1.48	2,20	•
792LT-20	1-1/4	31,5	1.97	50	6000	42,0	17-1/2	445	2.48	3,69	•
792LT-24	1-1/2	38	2.22	57	6000	42,0	20-3/4	530	3.22	4,79	•

Application: Petroleum base hydraulic fluids and lubricating oils.

Inner Tube: Synthetic rubber.

Reinforcement: Four or six spiral wires, high tensile steel

Cover: PKR Rubber.

Temperature Range: -70°F to +212°F (-57°C to +100°C).

Fittings: 79 Series - pg. B-127.

- See Section C for Parkrimp Assembly Instructions.
- Temperature Range of other media listed in Section E.

A

B

C

D

E