



## AIRTEMP 220

Hot air delivery hose designed for compressors and pneumatic systems like flexible connection between motor blower and road tanker used for dry pellets, abrasive powders and granular material transport.

### Hose Construction

- Tube:** Black, smooth, insulating, EPR rubber compound with very good resistance to high temperature
- Reinforcement:** Synthetic textile fabrics yarns
- Cover:** Black (N), smooth, insulating, wrapped finish EPDM rubber compound, resistant to heat, abrasion, ozone and weather



- Wide temperature range
- Insulating hose
- Could be complementary to CERGOM
- Burst Pressure Value 3:1

### Tolerances

According to RMA steel mandrel  
Refer to Technical Handbook on page TH34

### Temperature Range

-40 °C (-40 °F) to +220 °C (+435 °F)  
with peaks to +240 °C (+465 °F)

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH36346010/40	51	69	1.0	145	10.0	1.85	350	N
IH36346011/40	60	78	1.0	145	10.0	2.13	420	N
IH36346012/20	65	83	1.0	145	10.0	2.40	455	N
IH36346013/20	75	93	1.0	145	10.0	2.62	550	N
IH36346014/20	80	98	1.0	145	10.0	2.65	600	N