



E-Z FORM GS

Designed to handle air, coolant, mild chemicals and water. Extremely flexible, lightweight provides full suction capability and a path to conduct a static electrical charge to ground. The unique Greek cover corrugations provides minimal force-to-bend, superior kink resistance, and maximum flexibility for ease of handling, used where formed hose might normally be required.

Hose Construction

- Tube:** Black EPDM, antistatic rubber compound
- Reinforcement:** Multiple textile plies with wire helix
- Cover:** Black EPDM rubber compound resistant to weathering, greek corrugated finish



- Saves time and costs thanks to easy and quick assembly
- Superior kink resistance, minimal force to bend, outstanding flexibility
- Performance equal to SAE J20R2-D1
- Burst Pressure Value 4:1
- Vacuum: 0.9 bar

Tolerances

According to UNI EN ISO 1307
Refer to Technical Handbook on page TH34

Temperature Range

-40 °C (-40 °F) to +125 °C (+257 °F)

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH73950500/10	13	23	0.5	75.0	5	0.33	35	Y
IH73950594/10	15	25	0.5	75.0	5	0.36	45	Y
IH73950625/10	16	26	0.5	75.0	5	0.39	45	N
IH73950750/10	19	29	0.5	75.0	5	0.46	50	Y
IH73951000/10	25	35	0.5	75.0	5	0.56	50	Y
IH73951125/10	29	38	0.5	75.0	5	0.62	65	Y
IH73951250/10	32	43	0.5	75.0	5	0.75	80	Y
IH73951375/10	35	46	0.5	75.0	5	0.79	95	Y
IH73951500/10	38	49	0.5	75.0	5	0.85	100	Y
IH73952000/10	51	63	0.5	75.0	5	1.44	150	Y
IH73952250/10	57	70	0.5	75.0	5	1.61	200	Y
IH73952375/10	60	73	0.5	75.0	5	1.64	210	Y
IH73952500/10	63.5	76.5	0.5	75.0	5	1.74	220	Y
IH73953000/10	76	90	0.5	75.0	5	2.23	270	Y
IH73954000/10	102	116	0.5	75.0	5	3.28	400	Y