

Table of Contents

<u>GH134W</u>	<u>G-2</u>	<u>H757</u>	<u>G-2</u>
---------------	------------	-------------	------------



GH134W Multi-Refrigerant Hose

SAE J2064 Type E, Class 1



# Part Number	Hose I.D.			Hose O.D.			Working Pressure		Min. Burst Pressure		Min. Bend Radius		Hose Weight		Avail. Lengths
	mm	in	fraction	mm	in	fraction	bar	psi	bar	psi	mm	in	Kg/m	lbs/100ft	
GH134-6WR50 GH134-6WR200	7,9	0.31	5/16	14,7	0.58	37/64	34,5	500	137,9	2,000	50,8	2.00	4,1	9	50 200
GH134-8WR50 GH134-8WR200	10,3	0.41	13/32	17,8	0.70	45/64	34,5	500	137,9	2,000	63,5	2.50	5,5	12	50 200
GH134-10WR50 GH134-10WR200	12,7	0.50	1/2	19,8	0.78	25/32	34,5	500	137,9	2,000	76,2	3.00	6,8	15	50 200
GH134-12WR50 GH134-12WR200	15,9	0.63	5/8	24,9	0.98	63/64	34,5	500	137,9	2,000	101,6	4.00	8,2	18	50 200
*GH134-16WR50 *GH134-16WR200	22,2	0.875	7/8	31,2	1.23	1-11/50	34,5	500	137,9	2,000	127,0	7.00	10,0	22	50 200

Temp. Range:

- 40°C to +135°C
(- 40°F to +275°F)

Typical Application:

Transportation, refrigeration and air conditioning systems.

R404a Effusion:

.8 kg./m²/yr. at 60°C
(.2 lbs./ft²/yr. at 140°F)

HFC 134a Effusion:

2.42 kg./m²/yr. at 80°C
(.50 lbs./ft²/yr. at 176°F)

R407C Effusion:

20 kg./m²/yr. at 80°C

Moisture Ingression:

.013/cm²/yr. (.08 gm./in²/yr.)

For more information on EZ Clip, see document #W-HOAC-MC001-E3

Hose available in reels, by ordering part number, size and WRL

Hose Fitting Reference

EZ Clip

Series

Page

K-32-64

G

Hose - Air Conditioning

H757 Air Conditioning Hose

SAE J2064 Type C, Class 1



# Part Number	Hose I.D.			Hose O.D.			Working Pressure		Min. Burst Pressure		Min. Bend Radius		Hose Weight		Avail. Lengths
	mm	in	fraction	mm	in	fraction	bar	psi	bar	psi	mm	in	Kg/m	lbs/100ft	
H75706 H75706-100 H75706-250	7,9	0.31	5/16	14,3	0.56	9/16	27,6	400	137,9	2,000	50,8	2.00	4,5	10	50 100 250
H75708 H75708-100 H75708-250	10,3	0.41	13/32	17,5	0.69	11/16	27,6	400	137,9	2,000	63,5	2.50	5,4	12	50 100 250
H75710 H75710-100 H75710-250	12,7	0.50	1/2	19,1	0.75	3/4	24,1	350	120,7	1,750	76,2	3.00	5,9	13	50 100 250
H75712 H75712-100 H75712-250	15,9	0.63	5/8	23,8	0.94	15/16	24,1	350	120,7	1,750	101,6	4.00	10,4	23	50 100 250

Inner Tube:

Rubber/Nylon/Rubber

Reinforcement:

1 Fiber Braid

Cover: Butyl (perforated)

Temp. Range:

-30°C to +120°C
(-22°F to +248°F) for R12;
-30°C to +125°C (-22°F to +257°F) for R134a

Typical Application:

A refrigerant hose recommended for R134a and R12 applications. Ideal for heavy duty truck use as well as industrial and automotive applications.

Hose Fitting Reference

C-O-C

757 'E' Series

Page

J-24-31