



JETCORD XT/C

According to API 1529

Designed for use in all operations associated with the ground refuelling of aircraft non-electrically bonded, but incorporating an antistatic cover compound.

Hose Construction

Tube: Black, smooth, NBR rubber compound, resistant to aviation fuels having an aromatic content not exceeding 50 %

Reinforcement: Synthetic textile fabrics

Cover: Black, antistatic ($R > 10^3 < 10^6 \Omega/m$), CR rubber compound, resistant to mineral oil, fuels, abrasion, ozone and weathering



- Customized length and assembly with safety clamps
- Suggested brass fitting to prevent sparks
- Supplied with test report
- Burst Pressure Value 4:1






Tolerances

According to API 1529

Refer to Technical Handbook on page TH34

Temperature Range

-40 °C (-40 °F) to +70 °C (+158 °F)

Part Number	 I.D. (mm)	 O.D. (mm)	 Working Pressure			 Weight kg/m	 min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH36522802/0	25	38.5	2.0	300.0	20	0.90	125	N
IH36522801/0	32	45.5	2.0	300.0	20	1.09	160	N
IH36522803/0	38	51.5	2.0	300.0	20	1.28	190	N
IH36522434/0	50	67	2.0	300.0	20	2.02	250	N
IH36522435/0	63.5	80	2.0	300.0	20	2.48	310	N
IH36522804/0	75	92	2.0	300.0	20	2.88	375	N
IH36522800/0	100	122	2.0	300.0	20	5.01	500	N