



# MINIERA 10

*Suitable for compressed air tools (with minimal oil traces) in factories and designed for quarries, building and mining industries.*

## Hose Construction

**Tube:** Black, oil mist resistant, smooth SBR nitrosamine free rubber compound

**Reinforcement:** Synthetic textile fabrics

**Cover:** Black, abrasion, ageing and weather-resistant SBR nitrosamine free rubber compound



- Also suitable for water and air in general service applications
- Nitrosamine free compounds
- Burst Pressure Value 3:1








## Temperature Range

-30 °C (-22 °F) to +80 °C (+176 °F)

## Tolerances

According to RMA steel mandrel  
Refer to Technical Handbook on page TH34

Part Number	 I.D. (mm)	 O.D. (mm)	 Working Pressure			 Weight	 min. Bend Radius	in Stock
			MPa	psi	bar			
IH36342181/40	25	35	1.0	150.0	10	0.70	250	Y
IH36342182/40	30	40	1.0	150.0	10	0.81	300	N
IH36342184/40	35	45	1.0	150.0	10	0.92	350	Y
IH36342185/40	40	50	1.0	150.0	10	1.02	400	Y
IH36342186/40	45	55	1.0	150.0	10	1.14	450	N
IH36342187/40	50	60	1.0	150.0	10	1.25	500	Y
IH36342188/40	60	70	1.0	150.0	10	1.47	600	N
IH36342189/20	70	80	1.0	150.0	10	1.68	700	N
IH36342190/40	75	86	1.0	150.0	10	1.99	750	N
IH36342190/20	75	86	1.0	150.0	10	1.99	750	N
IH36342191/20	100	112	1.0	150.0	10	2.86	1000	N
IH36342194/20	102	114	1.0	150.0	10	2.99	1020	N