



## MINIERA 40

Compressed air for mine and quarries, designed for long lasting service and maximum safety in heavy duty applications.

### Hose Construction

**Tube:** Black, NBR rubber compound, oil resistant

**Reinforcement:** One special braid of steel wire

**Cover:** Black SBR/CR rubber compound, abrasion, oils, ozone and weather resistant



- Heavy duty application
- Specific for compressed air tools in mining
- Low temperature resistance
- Burst Pressure Value 4:1

### Temperature Range

-40 °C (-40 °F) to +100 °C (+212 °F)

### Tolerances

According to BS 5118/34310  
Refer to Technical Handbook on page TH34

Part Number	Nominal Diameter		O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
	(mm)	(inch)		MPa	psi	bar			
IH36348001/40	13	½	23	4.0	580.0	40	0.55	150	N
IH36348002/40	19	¾	30	4.0	580.0	40	0.77	230	N
IH36348003/40	25	1	38	4.0	580.0	40	1.06	300	N
IH36348004/40	32	1 ¼	46	4.0	580.0	40	1.45	380	N
IH36348005/40	38	1 ½	52	4.0	580.0	40	1.80	455	N
IH36348000/40	51	2	66	4.0	580.0	40	2.30	600	N