



APERFRUT 20 - 40 - 80

For delivery of air, water and all fungicide products. Particularly suitable for spraying in agriculture. Resistant to compressor oil-mist.

Hose Construction

Tube: Black, smooth, PVC compound
Reinforcement: Synthetic textile yarns
Cover: Orange (20), red (40) and blue (80), smooth, abrasion, and weather-resistant PVC compound

Temperature Range






-15 °C (+5 °F) to +60 °C (+140 °F)



- Colored cover to distinguish WP level
- Multiple fluids for various industrial applications
- Burst Pressure Value 3:1 for 20 and 40 bar
- Burst Pressure Value 2.5:1 for 80 bar

Tolerances

Refer to Technical Handbook on page TH34

Part Number	 I.D. (mm)	 O.D. (mm)	 Working Pressure			 Weight kg/m	 min. Bend Radius mm	in Stock
			MPa	psi	bar			
APERFRUT 20								
IH35040010/100	8	13	2.0	300.0	20	0.11	30	Y
IH35040012/100	10	15	2.0	300.0	20	0.14	55	Y
IH35040014/100	13	19	2.0	300.0	20	0.20	85	Y
IH35040015/100	16	23	2.0	300.0	20	0.29	90	N
IH35040016/100	19	26.5	2.0	300.0	20	0.33	100	Y
APERFRUT 40								
IH35040260/100	8	14	4.0	600.0	40	0.14	30	Y
IH35040261/100	10	16	4.0	600.0	40	0.17	50	Y
IH35040114/100	13	21	4.0	600.0	40	0.29	80	Y
APERFRUT 80								
IH35040268/100	8	15	8.0	1200.0	80	0.17	25	Y
IH35040270/100	10	18	8.0	1200.0	80	0.23	45	Y
IH35040214/100	13	23	7.0	1015.0	70	0.38	60	Y

APERFRUT 20 bar PARKER

APERFRUT 40 bar PARKER

APERFRUT 80 bar PARKER