



# ARCTIC-EDGE

## Parker Global Product

*Recommended suitable for air, mild chemicals, water, oil, biodiesel, diesel, ethanol and gasoline to be used in refrigerated applications and cold weather conditions. For agriculture, construction and general industrial. Do not use for fuel dispensing.*

### Hose Construction

**Tube:** Black NBR rubber compound.  
**Reinforcement:** Multiple textile plies with static wire  
**Cover:** Black, smooth CR rubber compound resistant to oil and weathering

### Temperature Range

-57 °C (-70 °F) to +100 °C (+212 °F)



- High flexibility and kink resistance at extreme low temperatures
- Conductive hose with copper wire
- Cover incorporates a longitudinal blue stripe for easy identification
- Burst Pressure Value 4:1

### Tolerances

According to UNI EN ISO 1307  
 Refer to Technical Handbook on page TH34

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH710238304/40	9.5	19	2.0	300.0	20	0.10	96	N
IH710250304/40	13	23	2.0	300.0	20	0.13	127	N
IH710275304/40	19	29.5	2.0	300.0	20	0.17	152	Y
IH7102100304/40	25	37	2.0	300.0	20	0.24	203	Y
IH7102125304/40	32	46	2.0	300.0	20	0.38	228	Y
IH7102138304/40	35	49	2.0	300.0	20	0.40	241	N
IH7102150304/40	38	51.5	2.0	300.0	20	0.42	254	Y