



ASPIREX

Suitable for suction of air, dust, fumes, saw-dust and wood-shavings. Also suitable for centralized suction equipment in wood, textile, china and welding equipment. It is also suitable for use on agricultural machinery.

Hose Construction

Flexible hose having a grey, rigid PVC spiral embedded in a metalized grey, flexible PVC wall. Externally corrugated, smooth inner surface. Self-extinguishing according to UL 94 Class V2.

Temperature Range






-15 °C (+5 °F) to +60 °C (+140 °F)



- Self-extinguishing hose
- General purpose hose
- Not to be used under pressure
- Vacuum 0.75 bar for ID up to 50 mm then 0.40 bar

Tolerances

Refer to Technical Handbook on page TH34

Part Number				Working Pressure					in Stock
	I.D. (mm)	Wall (mm)	MPa	psi	bar	kg/m	min. Bend Radius (mm)		
IH35560020/50	20	2.6	–	–	–	0.14	20	Y	
IH35560025/50	25	2.9	–	–	–	0.18	25	Y	
IH35562032/50	32	3.3	–	–	–	0.27	32	Y	
IH35560040/50	40	3.9	–	–	–	0.36	40	Y	
IH35560050/50	50	4.2	–	–	–	0.52	50	Y	
IH35560060/50	60	4.4	–	–	–	0.64	60	Y	
IH35560070/50	70	4.8	–	–	–	0.76	70	Y	
IH35560080/50	80	5.0	–	–	–	0.97	80	Y	
IH35560100/30	100	5.3	–	–	–	1.27	100	Y	
IH35560120/30	120	5.6	–	–	–	1.58	120	Y	
IH35560150/30	150	5.9	–	–	–	2.15	150	Y	
IH35562160/30	160	6.1	–	–	–	2.28	160	N	
IH35560200/15	200	7.0	–	–	–	2.95	200	Y	
IH35560250/15	250	8.0	–	–	–	4.00	250	N	

ASPIREX I.D. mm - SELF-EXTINGUISHING UL 94 V2 PARKER