



CARBO G NW/L 10 – NB/R 10

According to UNI 7140

Connection of household appliances to the gas line (NW/L) or to LPG bottles (NB/R).

Hose Construction

Tube: Black, smooth NBR rubber compound, suitable for Domestic Gas

Reinforcement: Synthetic textile yarns

Cover: White (NW) or blue (NB), ageing-resistant, smooth (/L) or ribbed (/R) SBR/EPDM rubber compound

Temperature Range

-20 °C (-4 °F) to +90 °C (+194 °F)








- Quarterly tested by IMQ (Italian Institute of Quality Approval)
- Low permeability
- Superior tensile strength
- White smooth cover for indoor and blue ribbed cover for outdoor
- Burst Pressure Value 3:1

Tolerances

According to UNI 7140

Refer to Technical Handbook on page TH34

Part Number	 I.D. (mm)	 O.D. (mm)	 Working Pressure	Working Pressure			 Weight	 min. Bend Radius	in Stock
				MPa	psi	bar			
CARBO G NB/R 10									
IH30551594/100	8	13	1.0	150.0	10	0.13	33	Y	
CARBO G NW/L 10									
IH30551600/100	13	20	1.0	150.0	10	0.29	51	Y	

CARBO G UNI 7140 – I.D. – IMQ – DA SOSTITUIRE ENTRO IL ... - MADE IN ITALY



CARBO G UNI 7140 – I.D. – IMQ – DA SOSTITUIRE ENTRO IL ... - MADE IN ITALY

