



CEMENT SM 10

Suitable for suction and delivery of dry cement to road tankers and storage bins or silos.

Hose Construction

Tube: Black, antistatic smooth abrasion resistant BR/NR rubber compound, abrasion max. 60 - 70 mm³

Reinforcement: Synthetic textile fabrics, embedded steel wire helix

Cover: Black, abrasion and weather-resistant, SBR rubber compound






- In-plant transfer/loading, bulk transport trucks
- Construction, general industry
- Good flexibility
- Vacuum 0.8 bar
- Burst Pressure Value 3:1

Temperature Range

-30 °C (-22 °F) to +70 °C (+158 °F)

Tolerances

According to RMA steel mandrel
Refer to *Technical Handbook* on page TH34

Part Number				Working Pressure					in Stock
	I.D. (mm)	O.D. (mm)		MPa	psi	bar			
IH36923100/40	50	64	0.1	150.0	10	1.92	300	Y	
IH36923101/40	60	74	0.1	150.0	10	2.26	360	N	
IH36923105/20	75	93	0.1	150.0	10	3.53	450	N	
IH36923102/20	100	118	0.1	150.0	10	4.80	600	Y	
IH36923109/20	120	140	0.1	150.0	10	6.54	720	N	
IH36923107/20	125	143	0.1	150.0	10	5.77	750	N	