



DRINKPRESS 164

Recommended for delivery of all foodstuffs containing animal or vegetable fats and oils as well as beverages and liqueurs. Ideal for cleaning dairies, slaughter houses, food processing plants with hot water and steam.

Hose Construction

- Tube:** White, smooth NBR rubber compound, non-toxic, odorless and taste-free.
Resistant to steam and hot water
- Reinforcement:** Synthetic textile yarns
- Cover:** Blue, smooth NBR/PVC rubber compound. Oils, grease, abrasion and weather-resistant. Pin-pricked cover to prevent blisters during use.



- According to FDA, DM 21/03/73
- Versatility of use for a logistic benefit
- Burst Pressure Value 3:1 for water
- Burst Pressure Value 10:1 for steam






Tolerances

According to UNI EN ISO 1307
Refer to Technical Handbook on page TH34






Temperature Range

-20 °C (+4 °F) to +95 °C (+203 °C) for foodstuffs
up to +164 °C (+327 °F) for hot water & steam only

For foodstuffs

Part Number	 I.D. (mm)	 O.D. (mm)	 Working Pressure			 Weight kg/m	 min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH30240051/40	10	19	2.0	300.0	20	0.31	80	N
IH30240052/40	13	23	2.0	300.0	20	0.42	105	Y
IH30240053/40	16	26	2.0	300.0	20	0.49	130	N
IH30240054/40	19	31	2.0	300.0	20	0.71	150	Y
IH30240055/40	25	39	1.0	150.0	10	1.05	200	N

For hot water & steam

Part Number	 I.D. (mm)	 O.D. (mm)	 Working Pressure			 Weight kg/m	 min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH30240051/40	10	19	0.6	87.0	6	0.31	80	N
IH30240052/40	13	23	0.6	87.0	6	0.42	105	Y
IH30240053/40	16	26	0.6	87.0	6	0.49	130	N
IH30240054/40	19	31	0.6	87.0	6	0.71	150	Y
IH30240055/40	25	39	0.3	44.0	3	1.05	200	N