



# GAMBRINUS RED 10

Recommended for wine, beer, liqueurs, fruit juice and soft drinks in process, package and transfer phase. Ideal either fixed and mobile installation. Not suitable for fatty food.

## Hose Construction

**Tube:** White, smooth EPDM rubber compound, non-toxic, odorless and taste-free.  
Manufactured on stainless steel mandrel for the maximum cleanliness and hygienic standards

**Reinforcement:** Synthetic textile fabrics

**Cover:** Red EPDM rubber compound, non-marking, abrasion and weather-resistant






- According to FDA, BfR class 2, DM 21/03/73, EC 1935/2004
- Up to 96 % alcoholic content
- ADI free
- Crimped Stainless Steel Fittings available
- Burst Pressure Value 3:1

## Tolerances

According to RMA steel mandrel  
Refer to Technical Handbook on page TH34

## Temperature Range

-40 °C (-40 °F) to +120 °C (+248 °F)  
sterilization at 110 °C for max 30 min.

Part Number								in Stock
	I.D. (mm)	O.D. (mm)	MPa	psi	bar			
IH36242531/40	19	29	1.0	150.0	10	0.45	95	N
IH36242532/40	25	35	1.0	150.0	10	0.59	140	N
IH36242533/40	30	41	1.0	150.0	10	0.80	160	N
IH36242534/40	32	43	1.0	150.0	10	0.90	170	N
IH36242535/40	38	51	1.0	150.0	10	1.20	200	N
IH36242536/40	40	54	1.0	150.0	10	1.40	220	N
IH36242537/40	51	65	1.0	150.0	10	1.90	250	N
IH36242538/40	60	76	1.0	150.0	10	2.50	320	N
IH36242539/40	63.5	81	1.0	150.0	10	2.60	340	N