



PROPANPRESS EN ISO 3821 N/L 20

According to EN ISO 3821

Suitable for LPG in industrial applications.

Hose Construction

Tube: Black, LPG resistant smooth NBR rubber compound

Reinforcement: Synthetic textile yarns

Cover: Orange, smooth PVC/NBR rubber compound resistant to ageing and weathering, pin-pricked cover to prevent blisters during use



- Pin-pricked cover
- Low permeation
- Orange cover following specs indication
- Flexible hose for easy handling
- Burst Pressure Value 3:1

Temperature Range

-30 °C (-22 °F) to +70 °C (+158 °F)

Tolerances

According to EN ISO 3821

Refer to *Technical Handbook* on page TH34

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH30413456/100	6.3	13.3	2.0	300.0	20	0.16	50	Y
IH30413457/100	8	15	2.0	300.0	20	0.18	65	Y
IH30413459/100	8.5	16	2.0	300.0	20	0.21	70	Y
IH30413458/100	10	17	2.0	300.0	20	0.22	80	Y

RUBBER HOSE PROPANPRESS EN ISO 3821 - 2MPa (20 bar) - I.D. - MADE IN ITALY (Year with the traceability code)